

**INTERNAL PARTITION KITS – PERFORMANCE CHART**

Holder of certificate: DEKO Partitions ltd of Denmark  
Maarkaervej 11  
DK-2630 Taastrup

Certificate number: 289

Date of issue: 2011-10-07

Scope of certificate updated: 2011-10-07

**For products covered by the above-mentioned certificate, the performance shall be declared in accordance with the below table:**

Product type	Product description	Relevant ETA	Reaction to fire Euroclass EN13501-1	Resistance to fire class EN 13501-2
1090	Steel framework with a single layer of gypsum plasterboards on both sides	03/0002	B-s2, d0	EI 30
1090 PF	Steel framework with a single layer of gypsum plasterboards on both sides	03/0002	B-s2, d0	EI 30
1090 Glazed	Glazed partition with glass panes classified as E30	03/0002	A1	E 30
1090 Glazed	Glazed partition with glass panes classified as EI30	03/0002	A1	EI 30
1290	Steel framework with a double layer of gypsum plasterboards on both sides	03/0002	B-s2, d0	EI 60
1290 PF	Steel framework with a double layer of gypsum plasterboards on both sides	03/0002	B-s2, d0	EI 60
1290 Glazed	Glazed partition with glass panes classified as EI60	03/0002	A1	EI 60
FG-Fire	Fully glazed partition with 20 mm glass panes classified as EW30	10/0224	A1	EW 30
FG-Fire	Fully glazed partition with 23 mm glass panes classified as EI30, EW60	10/0224	A1	EI 30/EW 60
FG-Fire	Fully glazed partition with 28 mm glass panes classified as EI60, EW60	10/0224	A1	EI 60 / EW 60
*DEKO door	Fire rated single leaf door, 30 minutes resistance	-	-	EI <sub>2</sub> 30
*DEKO door	Fire rated single leaf door, 60 minutes resistance	-	-	EI <sub>2</sub> 60

\* Products marked with asterisk are not covered by any of the ETAs but classified in accordance with EN 13501-2

Date: 2011-10-07

Signature: 